

TECH DATA SHEET

APLITAPE 4050

HEAVYWEIGHT PAPER APPLICATION TAPE

4050 is standard weight saturated paper coated with a medium tack rubber adhesive designed specifically as a premasking of mid-sized die cut or prespaced vinyl and printed graphics.

PHYSICAL SPECIFICATIONS

Adhesive	Rubber-based
Color	White/Translucent
Caliper <i>facestock</i>	100-113 microns (4.0 -4.5 mils)
Caliper <i>facestock + adhesive</i>	125-138 microns (5.0 - 5.5 mils)
Adhesion to Steel*	13 - 15 N/100mm (12 - 14 oz.)
Tensile	297 N/100mm (17lb./in)
Elongation	3-4%
Tear Resistance	50
Shelf Life**	1 year

FEATURES

- Removes easily following graphics application.
- If adhesive touches adhesive, Conform pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.

APPLICATIONS

- Premask for small and medium size vinyl graphics.
- All-purpose application tape for wet and dry applications.
- Excellent for transferring graphics to banners.

WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.



RTape Corp.
6 Ingersoll Road
South Plainfield, NJ 07080
T 1-800-440-1250
www.rtape.com

RESPONSIVE
RELIABLE
RESOURCEFUL