

## Avery Dennison® V-6750B Conspicuity Tape

### Prismatic Grade Conspicuity Tape for Enhanced Visibility and Vehicle Recognition - ECE 104 / Class C

Data Bulletin # PDB V-6750B

Dated: 10 May10

#### Description:

Avery Dennison® V-6750B Series reflective tape for use on pvc curtain sided vehicles. It is a high quality, durable, self-adhesive, prismatic cube corner retroreflective tape and is designed for use on vehicles for easy nighttime vehicle recognition and increased road safety. V-6750B complies with ECE 104, Class C requirements.

#### Construction:

Pre-Mask:	Polymeric film
Face Film:	Prismatic reflective film
Adhesive	Permanent, acrylic pressure sensitive
Liner:	Polymeric film

#### Warranted Photometric Performance:

Minimum coefficient of retroreflection (R') in (cd / lx / m<sup>2</sup>) according to ECE 104, Class C

Observation Angle	Entrance Angle	White	Yellow	Red
0.33°	5°	450	300	120
	20°	/	/	60
	30°	200	130	30
	40°	90	75	10
	60°	16	10	/

Entrance angle is defined in C.I.E. notation by its  $\beta_2$  component.  $\beta_1$  &  $\epsilon$  are held at 0°.

#### Colors & Specification Limits (Daytime):

Daytime colorimetric requirements according to ECE 104, Class C.

Color	1		2		3		4		Luminance (Y%)	
	x	y	x	y	x	y	x	y	Min	Max
White	0.300	0.270	0.385	0.355	0.345	0.395	0.260	0.310	25	--
Yellow	0.545	0.454	0.487	0.423	0.427	0.483	0.465	0.534	16	--
Red	0.690	0.310	0.595	0.315	0.560	0.350	0.650	0.350	3	--

The four pairs of chromaticity coordinates and luminance range determine the acceptable color for new materials when measured with CIE Standard Illuminant D65 and 45°/0° geometry.

#### Colors & Specification Limits (Night-time):

Night-time colorimetric requirements according to ECE 104, Class C.

Color	1		2		3		4	
	x	y	x	y	x	y	x	y
White	0.417	0.359	0.373	0.402	0.450	0.513	0.548	0.414
Yellow	0.585	0.385	0.610	0.390	0.520	0.480	0.505	0.465
Red	0.720	0.258	0.735	0.265	0.665	0.335	0.643	0.335

The four pairs of chromaticity coordinates determine the acceptable color for new materials when illuminated with CIE Standard Illuminant A at an entrance angle of  $\beta_1 = \beta_2 = 0$ , or, if this produces a colorless surface reflection, angle  $\beta_1 = 0$ ,  $\beta_2 = +5$ , and measured at an observation angle of  $\alpha = 0.33$ .

**Avery Dennison® V-6750B continued...**
**Other Specifications:**

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

**Physical Properties:**

<b>Outdoor Durability</b>	3 years when properly processed and applied (vertical exposure).
<b>Minimum Surface &amp; Ambient Air Application Temperature</b>	16°C
<b>Application Surface</b>	Avery approved curtains, not older than 6 months. Wet method of application is not recommended for V-6750B.
<b>Service Temperature Range</b>	-40°C to 80°C
<b>Typical Film Caliper (w/Adhesive)</b>	230µm to 255µm
<b>Shelf Life</b>	One year when stored at the following temperature and conditions: 20° - 25°C and 50% ± 5% R.H.
<b>Other Tests</b>	Meets or exceeds applicable requirements outlined for ECE-104, Class C materials including color fastness, stability of photometric properties, resistance to weathering, corrosion, fuels, heat, cleaning and penetration of water.
<b>Application Guidelines</b>	<ul style="list-style-type: none"> <li>• Do not overlap sheeting</li> <li>• Application underneath belts or buckles is not recommended</li> <li>• Remove pre-mask using a 180° peel off angle</li> <li>• Curtain must remain undisturbed for 2 hours after application</li> <li>• Allow 72 hours before washing</li> </ul>

**Color & Size Configurations Available:**

<b>Color Availability</b>	V-6750B White V-6751B Yellow V-6772B Red
<b>Width</b>	50.8 mm wide roll
<b>Roll Length</b>	50 meters

*WARRANTY: All statements, technical information and recommendations about Avery Dennison products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that Purchaser has independently determined the suitability of such products for its purposes. Avery Dennison products are warranted to be free from defects in material and workmanship for either one year (or the period stated on the specific product information literature in effect at time of delivery, if longer) from date of shipment if said product is properly stored and applied. It is expressly agreed and understood that Avery Dennison's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited to repair or replacement of defective product without charge at Avery Dennison's plant or at the location of product (at Avery Dennison's election), or in the event replacement or repairs is not commercially practical, to Avery Dennison's issuing Purchaser a credit reasonable in light of the defect in the product.*

*Avery Dennison's liability for defective products shall not exceed the purchase price paid therefor by Purchaser and in no event shall Avery Dennison be responsible for any incidental or consequential damages whether foreseeable or not, caused by defects in such product, whether such damage occurs or is discovered before or after replacement or credit, and whether or not such damage is caused by Avery Dennison's negligence.*

*NO EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE (EXCEPT AS TO TITLE), OTHER THAN THOSE EXPRESSLY SET FORTH ABOVE WHICH ARE MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND MANUALLY SIGNED BY AN OFFICER OF AVERY DENNISON.*